Acecut 6000

Acecut 6000 is a washable cutting fluid for glass cutting. It is recommended when:

- cutting thick glass
- cutting automotive glass (shape cutting)
- cutting float glass online
- cutting shapes (high quality demands)

Specification

Density:	0.860 - 0,870 g/ml	DIN 51757 (20 °C)
Refractive index:	1.473 - 1.479	DIN 51432 (20 °C)
Viscosity:	60 - 74 mPas	DIN 54453 (20 °C)

Handling and Storage

Use suitable protective gloves when handling the product. Safety instructions for the handling can be found in the Material Safety Data Sheet.
Stored in well-closed containers at temperatures between 5 and 40 °C the minimum shelf life of Acecut 6000 is 1 year.

Dr. E/02-2018

CHEMETALL GMBH
Trakehner Straße 3
D-60487 Frankfurt a. M.
P. O. Box 90 01 70
D-60441 Frankfurt a. M.
Phone: +49 (69) 7165-0
Fax: +49 (69) 7165-3018
Internet: http://www.chemetall.com

Surface Treatment

® registered trademark
The above data have been compiled to the best of our knowledge on the basis of thorough tests and with regard to the current state of our long practical experience. No liabilities or guarantee deriving from or in connection with this leaflet can be imputed to us. - Reproduction, in whole or in part, only with our express permission.