

Glasscorp End Seal - Aerosol

1. 0 Description

Glasscorp End Seal Aerosol is a transparent resealing solution intended for use on pressure treated timber in above ground applications where cutting, notching, drilling, machining or other work exposes areas of unpenetrated wood. This product is only for supplementary application to timber that has been preservative treated in accordance with AS1604. This product is not suitable for application to or protection of untreated timber.

2.0 Direction for Use

For re-sealing of treated timber where cuts, notches, nail and drill holes have exposed fresh timber surfaces. For above ground use only.

1. Shake can well before use.
2. Hold can 150-200mm away from the surface to be sprayed.
3. Apply a wet saturation coat to ensure complete coverage of cut area. Apply a minimum of two coats, allowing 20 minutes drying before applying second coat.
4. Can be painted over when thoroughly dry. After application Glasscorp End Seal will seep into the wood and dry to a transparent colour.
5. If cutting pieces in advance, we recommend block staking and spraying end sections together. This will minimise overspray and wastage.
6. Over spray still wet: Clean up with Mineral Turpentine
7. Over spray that has dried: Allow 12 hours before over coating with either alkyd/oil based primer or acrylic primer/undercoat.
8. Note: Where the over spray is hard and shiny ensure you follow standard painting guidelines for surface preparation.

3.0 Storage

PRESSURISED DISPENSER. Store locked up. Protect from sunlight and do not expose to temperatures exceeding 50° C. Keep out of reach of children. Glasscorp End Seal

Aerosol is best used within 12 months from date of manufacture when stored in the above conditions in the original unopened container.

4.0 Safety & Handling

CAUTION: EXTREMELY FLAMMABLE

AEROSOL. Do not store or use near fire or flame. Do not spray on any incandescent material. Keep away from sources of ignition. Keep out of reach of children. Do not smoke during use. Use only with adequate ventilation. Avoid inhaling spray mist. Do not spray directly on humans, pets, food, food preparation surfaces or food utensils. Wash hands after use.

WARNING: INTENTIONAL MISUSE BY DELIBERATELY INHALING OR SNIFFING THE CONTENTS MAY BE HARMFUL OR FATAL.

5.0 First Aid

If medical advice is needed, have product container or label at hand. **IF ON SKIN** (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse. **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If exposed or concerned: Get medical advice/attention.

6.0 Packaging

Pressure cans: max 400ml net contents

7.0 Disposal of Empty Containers

Do not pierce or burn, even after use. Recyclable steel – recycle used cans if a facility is available or place used cans in household rubbish. See Safety Data Sheet for further information.

Glasscorp recommends pre-compatibility tests on substrates where End Seal has not been applied to before.